

SERA

LED surface type
wall mounted lighting fixture



The SERA's soft light creates strikingly beautiful light patterns and reveals stylistic finesse, which bewitches both owner and spectator. Thanks to SERA, areas can tell stories.

This almost magic effect is due to a very pragmatic approach, namely that extraordinary performance creates extraordinary effects. Its Contemporary design is perfect for enhancing residential and urban areas featuring a modern,

Contemporary design. It creates a direct light beam, thanks to its monodirectional optics, able to enhance a precise area or subject, without glare.

Characteristics

Aluminium Injection Body

Electrostatic Powder Paint

Optional RAL Colors

PMMA Diffuser

Aluminium PCB

LED with Life Span > 100.000 Hours

CCT tolerance within a 3 step MacAdams ellipse

Corrosion Protection (Optional)

5 Years Warranty

Marine Coating (Optional)

Key Advantages

- Graceful, unmistakable and powerful statement of light
- Economic and efficient
- Easy installation
- High performance LED
- High corrosion resistance
- UV Resistant Diffuser

Applications



Exterior



Facade




Architectural



Ancient

SERA




Standard Product

Input	220-240V / AC 50-60Hz
Control	On / Off
Optic	Symmetrical
Light Color	4000K
Body Color	9005 Black
CRI	>82
Protection	IP65
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,090
Weight	1 kg
Ambient Temperature	-30°C / +60°C

Available Options

Input	24V / DC
Control	DALI, DIM, DMX
Optic	Symmetrical
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP66 - IP67
Warranty	7-10 Years

Light Colors




Ordering Details


Product Code	Power	Light Color	Lumen
SERA.10.AC.N.4.30.9005	10W	4000K	1020
SERA.20.AC.N.4.30.9005	20W	4000K	2080
SERA.30.AC.N.4.30.9005	30W	4000K	3090

* For different options, please contact our team.

Body Colors Options



Light Effect



Product Coding

Product Name	Product Power	Input		Control System				Color Temperature			Light Beam	Body Color	
XX	XX	AC	DC	on/off	1-10V	PUSH	TRAC	DALI	3K	4K	6.5K	XX	XX
XX	XX	AC	DC	N	V	P	T	D	3	4	6	XX	XX