

# PANEL Slim 575

LED recessed type  
Slim panel lighting fixture





DKP sheet metal body  
Electrostatic coated  
Highly effective LGP  
UV protected diffuser  
Constant current LED driver  
Electrostatic powder coating paint  
Optional body colors  
ENEC Standards

Made in TURKEY




## BASIC OPTIONS


on/off	on/off Control (No Dimmable) Input
230V AC	Voltage 220-240V/AC - 50/60 Hz 5
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
	Light Beam 120°
	White Satin Polycarbonate Diffuser
°C	-20°C/+40°C Temperature

PRODUCT CODE	W	Lenght	Temp	Lumen*
PLS575.28P.575x575.N.4.120	40	575x575	4000K	3850
PLS575.36P.575x575.N.4.120	48	575x575	4000K	4620


## CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Transparent Diffuser	White Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN >90	CRI >90		W	E

## PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	
XX	XX	XX	N V P T D	3 4 6	XX

## TECHNICAL DRAWINGS



\* For different options, please contact our team.