

# ROSE GU

Floodlight Series



**A family of Adjustable floodlight designed in different sizes, Powers and light options. Perfect choice to meet the outdoor lighting requirements which need high technicality and captivating design.**

Floodlights for outdoor lighting ROSA GU, excellent performance in a compact, essential and sturdy design. Totally adjustable and equipped with a wide range of optics, ROSA GU floodlights are perfect for enhancing architectures and greeneries with accent lighting and decorative effects. It has Small-size, essential design, that integrates seamlessly into any environment. It is the GU version and can reach high Powers.

## Characteristics

Aluminium Injection Die Cast Body
Electrostatic Powder Coated
Optional RAL Colors
Adjustable Bracket
Heat & Impact Resistant Extra Clear 5mm Tempered Glass
Aluminium PCB
LED with Life Span > 100.000 Hours
CCT tolerance within a 3 step MacAdams ellipse
Corrosion Protection (Optional)
5 Years Warranty
Marine Coating (Optional)
Replaceable GU10 LED light source
ENEC Certified Driver

## Key Advantages

- Modern design
- Exceptional thermal system
- High optical precision
- Excellent light output
- High IP protection
- High Ambient temperature
- Easy installation

## Applications



Landscape



Architectural



Ancient



Bridges

# ROSE GU




## Standard Product

Input	100-240V / AC 50-60Hz
Control	On / Off
Optic	36°
Light Color	4000K
Body Color	7016 Grey
CRI	>82
Protection	IP66
Impact Resistance	IK09
Protection class IEC	Class I
Power factor (min.)	0,092
Surge protection	1KV
Weight	- kg
Ambient Temperature	-30°C / +60°C
Lamp Holder	GU10

## Available Options

Input	24V / DC
Control	RGB, DALI, DIM, DMX
Light Color	3000K, 4000K, 6500K
Body Color	Optional RAL colors
Glass	Frosted Diffuser Glass
CRI	>90
Protection	IP67-IP68
Impact Resistance	IK10
Warranty	7-10 Years

## Light Colors



\* Specifications according to OSRAM values.


## Ordering Details

Product Code	Power	Light Color	Beam Angle	Lumen
ROSA.GU.AC.N.4.36.7016	5W	4000K	36°	350

\* Specifications according to OSRAM values.


\*\* For different options, please contact our team.

## Beam Angle Options



\* Specifications according to OSRAM values.

## Body Colors Options



## Optional Accessories



## Product Coding

Product Name	Holder Type	Input	Control System	Color Temperature	Light Beam	Body Color
XX	XX	AC	on/off	3K	XX	XX
XX	XX	AC	1-10V	4K	XX	XX
XX	XX	AC	PUSH	6.5K	XX	XX
XX	XX	AC	TRIAC	XX	XX	XX
XX	XX	AC	DALI	XX	XX	XX
XX	XX	AC	XX	XX	XX	XX