

APOLLO-D

Outdoor surface type
LED Bollard Lighting



Outdoor surface type LED
Bollard Lighting
Aluminium body
PMMA acrylic light diffuser
High Efficiency LED Lighting
High quality silicon gasket
Anchor system
Optional body colors ENEC
Standards
IP66, IK08



BASIC OPTIONS

C/off	on/off Control (No Dimmable)
230V AC	Input Voltage 100-3050V AC 50/60 Hz
CRI >80	Rendering Index >80
B	Light Temperature 4000K
	Black Body Color
	-30°/55° C Temperature

PRODUCT CODE	W	D*L	Temp	Lumen*
APOLLOD.10.850.N.4	10	100*850	4000K	990
APOLLOD.26.1000.N.4	26	100*1000	4000K	1710

D: Diameter, L: Length
*According to 4000K light temperature

CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	All RAL codes
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90	B

PRODUCT CODING

Product Name	Product Power	Product Size	Control System				Color Temperature			Light Beam	
XX	XX	XX	C/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	
XX	XX	XX	N	V	P	T	D	3	4	6	XX

TECHNICAL DRAWINGS

