




ARCUS GU

recessed type
downlight



- Aluminium injection body
- High efficiency reflector
- Constant current LED driver
- Electrostatic powder coating paint
- Optional body colors
- ENEC standards



BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC, 50-60HZ
GU10	GU10 Socket
CRI >80	Color Rendering Index > 80
4K	Light Temperature 4000K
	Light Beam 36°
	Operating Temperature : -20 / 40 °C
w	White Body Color

PRODUCT CODE	W	Height	Lenght	Hole Size	Socket	Lumen*
ARCUS GU.X.75.N.X.X -		80	Ø89	80	GU10	-

* The information will vary depending on the bulb brand you prefer.


CUSTOMIZE OPTIONS

Dimmable TRIAC	Light Temperature 3000K	Light Temperature 6500K	Optional Body Color	Emergency KIT	Optional Reflector Color
DIM	3K	6.5K	B	E	R

PRODUCT CODING

Product Name	Product Power	Product Size	Control System					Color Temperature			Light Beam
XX	XX	XX	on/off	1-10V	PUSH	TRAC	DALI	3K	4K	6.5K	
XX	XX	XX	N	V	P	T	D	3	4	6	XX

TECHNICAL DRAWINGS



* For different options, please contact our team.