

# BULKHEAD

LED surfaced type  
circular LED lighting fixture



- Aluminum body
- Tempered Glass
- Constant current LED driver
- Electrostatic powder coating paint
- Optional body colors
- Motion Sensor-Optional
- ENEC Standarts



## BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220V/AC - 50/60 Hz
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
	Light Beam 120°
	White Satin Polycarbonate Diffuser
<b>B</b>	Black Body Color
°C	-20C°/+50C° Temperature

PRODUCT CODE	W	Temp	Lumen
BULKHEAD.3.15.N.4	3	4000K	285
BULKHEAD.5.15.N.4	5	4000K	475
BULKHEAD.7.15.N.4	7	4000K	665
BULKHEAD.10.15.N.4	10	4000K	950

\* According to 4000K light temperature



## CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Transparent Diffuser	White Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90		W	E

## PRODUCT CODING

Product Name	Product Power	Product Size	Control System					Color Temperature			Light Beam
XX	XX	XX	on/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	
XX	XX	XX	N	V	P	T	D	3	4	6	XX

## TECHNICAL DRAWINGS



\* For different options, please contact our team.