



CASU MAG DUO

magnetic type
Spotlight



Aluminium body
Aluminium extrusion heatsink
Nickel plated brass parts
Electrostatic powder coating paint
High performance COB LED High efficiency reflector
Optional body colors
ENEC standards



BASIC OPTIONS

| | |
|---------|--------------------------------------|
| on/off | on/off Control (No Dimmable) |
| 230V AC | Input Voltage 24V - 48V DC |
| CRI >80 | Color Rendering Index >80 |
| 4K | Light Temperature 4000K |
| ▲ | Light Beam 15°, 30°, 45° |
| 🌡️ | Operating Temperature : -20 / +40 °C |
| B | Black Body Color |


| PRODUCT CODE | W | Dia | Temp | Lumen* |
|----------------------------|----|-----|-------|--------|
| CASUMAGDUO.2x5.100.N.4.30 | 10 | Ø35 | 4000K | 1100 |
| CASUMAGDUO.2x7,5.270.N.4.3 | 15 | Ø35 | 4000K | 1650 |

CUSTOMIZE OPTIONS

| | | | | | | | | | | | |
|----------------|---------------|----------------|---------------|----------------------|-------------------------|-------------------------|-------------------------|-------------------------|---------------|----------------------------|---------------------|
| Dimmable 1-10V | Dimmable PUSH | Dimmable TRIAC | Dimmable DALI | Input Voltage 24V/DC | Light Temperature 2700K | Light Temperature 3000K | Light Temperature 4000K | Light Temperature 5000K | Dynamic White | Color Rendering Index > 90 | Optional Body Color |
| 1-10V | PUSH | TRIAC | DALI | 24V DC | 2.7K | 3K | 4K | 5K | DYN | CRI >90 | W |

PRODUCT CODING

| | | | | | |
|--------------|---------------|--------------|----------------|-------------------|------------|
| Product Name | Product Power | Product Size | Control System | Color Temperature | Light Beam |
| XX XX XX | XX | XX | N V P T D | 2 3 4 5 | XX |



* For different options, please contact our team.

TECHNICAL DRAWINGS

