


# CIRCLE L

Outdoor Type Decorative Lighting Poles



**Urban lighting between versatility and high visual comfort. CIRCLE L is the pole top luminaire for urban lighting, featuring a catchy shape and excellent performance, also available with the latest lighting technologies.**

Wide range of optics, powers and color temperatures to meet any lighting project need. Featuring an elegant, timeless design, excellent performance and fort he latest lighting designs. Its diffused wide optic provides a homogeneous, pleasant lighting with high visual comfort and no glare.

## Key Advantages

- Aluminium Body
- Smart energy savings
- Delivery of complete assembly
- Corrosion resistance

## Characteristics

Galvanized Steel
High efficiency LED lighting
Electrostatic powder paint
High quality silicone gasket
Galvanized metal anchorage
Aluminium PCB
LED with Life Span > 100.000 Hours
CCT tolerance within a 3 step MacAdams ellipse
Corrosion Protection
5 Years Warranty
Marine Coating (Optional)
ENEC Certified Driver

## Applications



Landscape




Outdoor



Urban

# CIRCLE L



## Standard Product


Input	100-305V / AC 50-65Hz
Control	On / Off
Optic	Symmetrical
Light Color	4000K
Body Color	7016 Grey
CRI	>82
Protection	IP66
Impact Resistance	IK08
Protection class IEC	Class I
Power factor (min.)	0,092
Weight	- kg
Ambient Temperature	-30°C / +60°C

## Available Options

\* Possibility of production in different lengths and sections.

Input	24V / DC
Control	RGB, DALI, DIM, DMX
Optic	8°, 15°, 30°, 50°, 60°, 70°, 90°, 120°, Asymmetrical
Light Color	2200K, 2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90
Protection	IP67
Warranty	7-10 Years


## Light Colors



## Body Colors Options



## Light Effect



## Optional Accessories



IP67  
Junction  
Box

## Ordering Details

Product Code	Power	Light Color	Dimensions	Lumen
<b>CIRCLE.L.20.4000.AC.N.4.SYM.7016</b>	20W	4000K	4000	2640
<b>CIRCLE.L.30.4000.AC.N.4.SYM.7016</b>	30W	4000K	4000	3960
<b>CIRCLE.L.80.4000.AC.N.4.SYM.7016</b>	80W	4000K	4000	10560
<b>CIRCLE.L.20.5000.AC.N.4.SYM.7016</b>	20W	4000K	5000	2640
<b>CIRCLE.L.30.5000.AC.N.4.SYM.7016</b>	30W	4000K	5000	3960
<b>CIRCLE.L.80.5000.AC.N.4.SYM.7016</b>	80W	4000K	5000	10560
<b>CIRCLE.L.20.6000.AC.N.4.SYM.7016</b>	20W	4000K	6000	2640
<b>CIRCLE.L.30.6000.AC.N.4.SYM.7016</b>	30W	4000K	6000	3960
<b>CIRCLE.L.80.6000.AC.N.4.SYM.7016</b>	80W	4000K	6000	10560
<b>CIRCLE.L.20.7000.AC.N.4.SYM.7016</b>	20W	4000K	7000	2640
<b>CIRCLE.L.30.7000.AC.N.4.SYM.7016</b>	30W	4000K	7000	1960
<b>CIRCLE.L.80.7000.AC.N.4.SYM.7016</b>	80W	4000K	7000	10560
<b>CIRCLE.L.20.8000.AC.N.4.SYM.7016</b>	20W	4000K	8000	2640
<b>CIRCLE.L.30.8000.AC.N.4.SYM.7016</b>	30W	4000K	8000	3960
<b>CIRCLE.L.80.8000.AC.N.4.SYM.7016</b>	80W	4000K	8000	10560

\* For different options, please contact our team.



## Product Coding

Product Name	Product Power	Input	Control System	Color Temperature	Light Beam	Body Color
XX	XX	AC DC	on/off 1-3 DV PUSH TRAC DALI	3K 4K 6.5K	XX	XX
XX	XX	AC DC	N V P T D	3 4 6	XX	XX