

ELA WALL LIGHT

Underwater lighting fixture



The elegant sobriety of ELA WALL, combined with state-of-the-art lighting technology, ensures its over-average versatility. It can easily be integrated in just about any environment and fulfils every requirement.

Made of Stainless Steel body with single cable entry, durable silicone rubber gasket and clear toughened glass

Key Advantages

- Can be easily integrated to many designs
- Economic and efficient
- Easy installation
- High performance LED
- High corrosion resistance

Characteristics

Stainless Steel body

High efficiency LED lighting

High quality silicone gasket

3 Step MacAdams

IP68, IK09

Applications



Landscape




Outdoor



Urban

ELA WALL LIGHT



* Possibility of production in different lengths and sections.


Standard Product

Input	24V / DC
Control	ON/OFF
Optic	30°
Light Color	4000K
Body Color	9006 Grey
CRI	>80
Protection	IP68
Impact Resistance	IK09
Working Temperature	-30°C / +60°C
Coating	Marine Grade

Light Colors



Body Colors Options



Optional Accessories



IP67
Junction
Box

Available Options

Input	220V / AC
Control	DMX- DALI
Optic	8°, 15°, 30°, 50°, 60°, 70°, 90°, 120°, Asymmetrical
Light Color	2700K, 3000K, 5000K, 6500K
Body Color	Optional RAL colors
CRI	>90

Ordering Details

Product Code	Power	Light Color	Dimension	Lumen
ELA.WALL.5.N.30	5W	4000K	Ø300	625
ELA.WALL.1€N.30	1€W	4000K	Ø300	1250
ELA.WALL.1GN.30	1GW	4000K	Ø300	1500
ELA.WALL.1i.N.30	1iW	4000K	Ø300	1875
ELA.WALL.1i.N.30	1iW	4000K	Ø300	2250
ELA.WALL.G€N.30	G€W	4000K	Ø300	2500
ELA.WALL.G.N.30	GW	4000K	Ø300	3125
ELA.WALL.G.N.30	GW	4000K	Ø300	3500
ELA.WALL.H€N.30	H€W	4000K	Ø300	3750

* For different options, please contact our team.

Product Coding

Product Name	Product Power	Module Pcs	Current	Product Height	Control System	Color Temperature	Light Beam	Body Color
XX	XX	XX	XX	XX	on/off SMART	3K 4K 5K 6.5K	XX	XX
XX	XX	XX	XX	XX	N S	3 4 5 6	XX	XX