


# KOZA M

surface type  
downlight



- Aluminium extrusion body
- UV protected diffuser
- Constant current LED driver
- Electrostatic powder coating paint
- Optional body colors
- ENEC standards



PRODUCT CODE	W	Height	Lenght	Temp	Lumen*
KOZAM.10.126.N.4.100	10	70	Ø126	4000K	1260

\* According to 4000K light temperature

## BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC, 50-60HZ
CRI >80	Color Rendering Index > 80
4K	Light Temperature 4000K
▲	Light Beam 120°
🌡️	Operating Temperature : -20 / 40 °C
w	White Body Color



## PRODUCT CODING

Product Name	Product Power	Product Size	Control System				Color Temperature			Light Beam	
XX	XX	XX	on/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	▲
XX	XX	XX	N	V	P	T	D	3	4	6	XX

## CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Optional Body Color	Optional Reflector Color	Emergency KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	B	R	E

## TECHNICAL DRAWINGS



\* For different options, please contact our team.