

Aluminium injection body
UV protected opal diffuser
Constant current LED driver
Electrostatic powder coating paint
Optional body colors
ENEC standards



BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC, 50-60HZ
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
	Light Beam 100°
	Operating Temperature : -20 / 40 °C
A	Aluminium Body Color

PRODUCT CODE	W	Height	Lenght	Hole Size	Temp	Lumen*
LUCE 3".8.125.N.4.100	8	50	Ø123	Ø130	4000K	820
LUCE 4".10.147.N.4.100	10	55	Ø147	Ø130	4000K	1180
LUCE 5".16.173.N.4.100	16	55	Ø173	Ø158	4000K	2000
LUCE 6".21.190.N.4.100	21	55	Ø190	Ø175	4000K	2600


* According to 4000K light temperature

CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index >90	Optional Body Color	3D Microprismatic Diffuser	Emergency KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90	B		E


PRODUCT CODING

Product Name	Product Power	Product Size	Control System				Color Temperature			Light Beam	
XX	XX	XX	PUSH	1-10V	TRIAC	DALI	3K	4K	6.5K		
XX	XX	XX	N	V	P	T	D	3	4	6	XX




TECHNICAL DRAWINGS

LUCE 3"




LUCE 4"



LUCE 5"



LUCE 6"



* For different options, please contact our team.