

# MIRE

wall type

erutxfi gnithgil raenil



- Aluminum extruded body
- UV protected diffuser
- Adjustable length steel ropes
- Constant current LED driver
- Electrostatic powder coating paint
- Production in different lengths
- Optional body colors
- ENEC Standards



PRODUCT CODE	W	Lenght	Temp	Lumen*
MIRE.15.600.N.4.120	15	600	4000K	1530
MIRE.24.900.N.4.120	24	900	4000K	2355
MIRE.30.1200.N.4.120	30	1200	4000K	3140
MIRE.36.1500.N.4.120	36	1500	4000K	3850
MIRE.45.1800.N.4.120	45	1800	4000K	5100

\* According to 4000K light temperature

## BASIC OPTIONS

- on/off Control (No Dimmable)
- Input Voltage 230V/AC
- Color Rendering Index > 80
- Light Temperature 4000K
- Light Beam 120°
- White Satin Diffuser
- Black Body Color



## PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	XX

## CUSTOMIZE OPTIONS

Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Transparent Diffuser	White Body Color	Grey Body Color
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90		W	G

## TECHNICAL DRAWINGS



\* For different options, please contact our team.