



- DKP sheet metal body
- UV protected diffuser
- Constant current LED driver
- Electrostatic powder coating paint
- Optional body colors
- ENEC standards



### BASIC OPTIONS

- on/off** on/off Control (No Dimmable)
- 230V AC** Input Voltage 220-240V/AC, 50-60HZ
- CRI >80** Color Rendering Index > 80
- 4K** Light Temperature 4000K
- Light Beam 120°**
- Operating Temperature** : -20 / 40 °C
- B** Black Body Color

PRODUCT CODE	W	Lenght	Temp	Lumen*
CARRE.36.596x596.N.4.120	36	596x596	4000K	4212

\* According to 4000K light temperature



### CUSTOMIZE OPTIONS

- Dimmable 1-10V** 1-10V
- Dimmable PUSH** PUSH
- Dimmable TRIAC** TRIAC
- Dimmable DALI** DALI
- Input Voltage 24V/DC** 24V DC
- Light Temperature 3000K** 3K
- Light Temperature 6500K** 6.5K
- Dynamic White** DYN
- Color Rendering Index > 90** CRI >90
- Optional Body Color** B
- Emergency KIT** E

### PRODUCT CODING

Product Name	Product Power	Product Size	Control System					Color Temperature			Light Beam
XX	XX	XX	on/off	1-10V	PUSH	TRAC	DALI	3K	4K	6.5K	Light Beam
XX	XX	XX	N	V	P	T	D	3	4	6	XX

### TECHNICAL DRAWINGS



\* For different options, please contact our team.