



- DKP sheet metal body
- UV protected diffuser
- Constant current LED driver
- Electrostatic powder coating paint
- Optional body colors
- ENEC standards



### BASIC OPTIONS

- on/off** on/off Control (No Dimmable)
- 230V AC** Input Voltage 220-240V/AC, 50-60HZ
- CRI >80** Color Rendering Index > 80
- 4K** Light Temperature 4000K
- Light Beam 120°**
- Operating Temperature** : -20 / 40 °C
- B** Black Body Color

PRODUCT CODE	W	Lenght	Temp	Lumen*
SYM.36.596x596.N.4.120	36	596x596	4000K	4212

\* According to 4000K light temperature



### CUSTOMIZE OPTIONS

- Dimmable 1-10V**
- Dimmable PUSH**
- Dimmable TRIAC**
- Dimmable DALI**
- Input Voltage 24V/DC**
- Light Temperature 3000K**
- Light Temperature 6500K**
- Dynamic White**
- Color Rendering Index > 90**
- Optional Body Color**
- Emergency KIT**

### PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off	3K	XX
XX	XX	XX	1-10V	4K	XX
XX	XX	XX	PUSH	6.5K	XX
XX	XX	XX	TRIAC	3K	XX
XX	XX	XX	DALI	4K	XX
XX	XX	XX	D	6.5K	XX
XX	XX	XX	N	3K	XX
XX	XX	XX	V	4K	XX
XX	XX	XX	P	6.5K	XX
XX	XX	XX	T	3K	XX
XX	XX	XX	D	4K	XX
XX	XX	XX	D	6.5K	XX

### TECHNICAL DRAWINGS



\* For different options, please contact our team.