



WALL LIGHT MAG

Magnetic type Walllight



- Aluminium body
- Aluminium extrusion heatsink
- Electrostatic powder coating paint
- High performance LED
- Opal pmma diffuser
- Optional body colors
- ENEC standards



BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 24V - 48V DC
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
▲	Light Beam 15°, 30°, 45°
🌡️	Operating Temperature : -20 / +40 °C
B	Black Body Color

PRODUCT CODE

PRODUCT CODE	W	Lengt	Temp	Lumen*
WALLMAG.10.138.N.4.120	10	138	4000K	1100
WALLMAG.10.138.N.4.120	15	138	4000K	1650


* According to 4000K light temperature

CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 2700K	Light Temperature 3000K	Light Temperature 4000K	Light Temperature 5000K	Dynamic White	Color Rendering Index > 90	Optional Body Color
1-10V	PUSH	TRIAC	DALI	24V DC	2.7K	3K	4K	5K	DYN	CRI >90	W

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	N V P T D	2 3 4 5	XX



TECHNICAL DRAWINGS



* For different options, please contact our team.