


AVUA DOUBLE GU

surface type
downlight



DKP Metal Body
GU10 Holder
Electrostatic powder coating paint
Optional body colors
ENEC Standards



BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
CRI > 80	Color Rendering Index > 80
4K	Light Temperature 4000K Light
▲	Beam 36°
W	White Body Color

PRODUCT CODE	W	Lenght	Temp	Lumen*
AUVADBL.GU10.220.N.4.36	GU10	220X85	-	-


* According to 4000K light temperature

CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Black Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI > 90	B	G

PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	on/off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	▲
XX	XX	XX	N V P T D	3 4 6	XX



TECHNICAL DRAWINGS



* For different options, please contact our team.