

ALERT


Surface type



- Aluminum extrusion body
- Aluminium injection heatsink
- Tempered Glass UV protected diffuser
- Constant current LED driver
- Electrostatic powder coating paint
- IP20 / IP44 / IP65 Options
- Optional body colors
- ENEC Standards



BASIC OPTIONS

DALI	DALI
28-36V AC	Input Voltage 28/36V
CRI >80	Color Rendering Index >85
4K	Light Temperature 3000K
	Light Beam 24° / 60° White
B	Matt Black Color


PRODUCT CODE	W	Height	Dia	Temp	Lumen*
ALERT.28.90.D.3.60	28	240	90	3000K	3010


* According to 3000K light temperature

CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	IP 65	Color Rendering Index > 90	Black Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	IP	CRI >90	B	G

PRODUCT CODING

Product Name	Product Power	Product Size	Control System				Color Temperature			Light Beam	
XX	XX	XX	on/off	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K	
XX	XX	XX	N	V	P	T	D	3	4	6	XX



TECHNICAL DRAWINGS



* For different options, please contact our team.