





Aluminum injection body,
UV protected diffuser,
Opal Polystyren/PMMA (Fire-
Proof) /Microprismatic (3D) Diffuser
Types, Constant current LED
driver, Electrostatic powder coating
paint, Optional body colors,
ENEC Standards



BASIC OPTIONS


on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 230V/AC
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
	Light Beam 95°
	White Polystyren Diffuser
w	White Body Color

PRODUCT CODE W HeightLength Hole Size Temp Lumen*


ESSO.6.111.N.4.95 6 75 Ø111 Ø95x95 4000K 660


* According to 4000K light temperature

CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index >90	Diffuser Options	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN >90	CRI >90		E

PRODUCT CODING

Product Name	Product Power	Product Size	Control System					Color Temperature			Light Beam
XX	XX	XX	1-10V	PUSH	TRIAC	DALI	3K	4K	6.5K		
XX	XX	XX	N	V	P	T	D	3	4	6	XX



TECHNICAL DRAWINGS



* For different options, please contact our team.