

LED Surface & Pendant type  
decorative lighting

Aluminum extruded body

Anodized coating

UV protected frosted diffuser

Adjustable length steel ropes

Nickel plated brass parts

Constant current LED driver

Electrostatic powder coating paint

Production in different lengths

Optional body colors

ENEC Standarts



## BASIC OPTIONS

on/off	on/off Control (No Dimmable)
230V AC	Input Voltage 220-240V/AC - 50/60 Hz 5
CRI >80	Color Rendering Index >80
4K	Light Temperature 4000K
	Light Beam 120°
	White Satin Polycarbonate Diffuser
B	Black Body Color
°C	-20°C/+40°C Temperature

PRODUCT CODE	W	Lenght	Temp	Lumen*
WEST.30.400.N.4.120	30	400	4000K	2460
WEST.45.600.N.4.120	45	600	4000K	3600
WEST.60.800.N.4.120	60	800	4000K	4920
WEST.75.1000.N.4.120	75	1000	4000K	6150
WEST.90.1200.N.4.120	90	1200	4000K	7380


\* According to 4000K light temperature

## CUSTOMIZE OPTIONS


Dimmable 1-10V	Dimmable PUSH	Dimmable TRIAC	Dimmable DALI	Input Voltage 24V/DC	Light Temperature 3000K	Light Temperature 6500K	Dynamic White	Color Rendering Index > 90	Transparent Diffuser	White Body Color	EMERGENCY KIT
1-10V	PUSH	TRIAC	DALI	24V DC	3K	6.5K	DYN	CRI >90		W	E

## PRODUCT CODING

Product Name	Product Power	Product Size	Control System	Color Temperature	Light Beam
XX	XX	XX	off 1-10V PUSH TRIAC DALI	3K 4K 6.5K	XX
XX	XX	XX	N V P T D	3 4 6	XX



## TECHNICAL DRAWINGS



\* For different options, please contact our team.